



PRODUCT DESCRIPTION

POLPO P360

Standard Tile Adhesive (C2TES1) :

- Polymer modified to provide a strong bond.
- Swimming Pool Wall and Floor Application.
- Improved workability.

POLPO P360 : a standard-setting cement-based polymer-modified tile adhesive POLPO.

POLPO P360 : classified as a C2TES1 under EN12004

APPLICATIONS:

POLPO C2TES1 is designed for fixing swimming pool tiles, Marble and Porcelain, Installing new ceramic tiles on old ones. tiles natural stone to All types of rigid cement-based surfaces as well as other pre-primed surfaces.

- swimming pool tiles.
- internal wall.
- External floor.
- External wall.
- All size tiles.

FEATURES AND BENEFITS:

- Low viscosity, therefore easily workable.
- Highly thixotropic.
- Can be applied on a vertical surface without sagging or letting heavy and large tiles slip.
- Tiles can be installed from the top towards the bottom without using spacer.
- Good capability to accommodate the different deformation of the covering from the substrate.
- Perfect adherence to all materials normally used in building.
- Hardens, even when very thickly applied, without appreciable shrinkage and dimensional changes.
- Particularly good extended open and adjustability time, facilitating installation.
- Can be used internally and externally.





PRODUCT DESCRIPTION

TYPICAL USE

- Suitable for use with large variety of tiles including ceramic, porcelain and natural stone tiles.
- Excellent workability and non-slip properties, ideal for fixing large format tiles.
- Ideal in showers, wet rooms, swimming pools and areas subject to prolonged wet conditions.
- Unaffected by frost after setting.

CHEMICAL CONTENT:

CHEMICAL CONTENT white Portland cement, graded sand, specific additive and resins.

RECOMMANDATIONS:

- Do not apply in wet weather, or in temperatures below 5°C or over 35°C.
- Wind reduces the tile cement open time and leads to reduced adherence.
- When fixing, it is important to press the tiles to make sure that they all form a solid surface, and to avoid any gaps between tile and support.
- Back buttering systematically in outdoor application
- Do not apply more than 15 mm or less than 5 mm thick.

Storage:

- Store in cool, dry place in a well-sealed container away from moist air for 24 months.
- Keep away from heat, ignition sources and from children.

Caution:

- Clean mixing container before use. Do not use dirty tools.
- Do not exceed dilution ratios.
- Keep out of the reach of children.

Health and safety Possible Hazards:

it causes irritation in case of skin contact & eye contact, flush immediately with plenty of water for at least 10 minutes and seek medical advice in case it happened.



TECHNICAL DATA

POWDER CARATERISTICS

Color:	white
Powder density (kg/m ³):	1350
Particle size:	≤ 0.350 mm
Reaction to fire:	Euroclass A1

PASTE CARATERISTICS

Mixing ratio:	± 25%
Paste density:	± 1.7
pH:	≥ 12
Pot life:	≤ 2
hours Open time:	≤ 30 min
Tile adjustment time:	≤ 20 min
Application temperature:	+5C to +35C

HARDEN PRODUCT CARATERISTICS

Bed thickness:	2 to 10mm
Joint filling:	≥ 24 hours
Light foot traffic:	≥ 24 hours
Full load traffic:	≥ 48 hours

CEMENT-BASED ADHESIVE C2TES1

EN 12004-2:2017

Initial tensile adhesion strength:	≥ 1 MPa
Tensile adhesion strength after open time :	≥ 1 MPa
Tensile adhesion strength after water immersion:	≥ 1 MPa
Tensile adhesion strength after heat ageing:	≥ 1 MPa

Note: setting times are quoted at 20°C and are temperature and humidity dependent

